

Electrostatic Equations for Dielectrics in MKSA and CGS-Gauss Units

THE DISPLACEMENT FIELD AND THE GAUSS LAW:

In MKSA units:

$$\mathbf{D} = \epsilon_0 \mathbf{E} + \mathbf{P} \quad (1)$$

$$\nabla \cdot \mathbf{D} = \rho_{\text{free}} \quad (2)$$

In CGS-Gauss units:

$$\mathbf{D} = \mathbf{E} + 4\pi \mathbf{P} \quad (3)$$

$$\nabla \cdot \mathbf{D} = 4\pi \rho_{\text{free}} \quad (4)$$

SUSCEPTIBILITY, PERMITTIVITY, AND THE DIELECTRIC CONSTANT:

In MKSA units:

$$\mathbf{P} = \chi \epsilon_0 \mathbf{E} \quad (5)$$

$$\mathbf{D} = \epsilon_{\text{abs}} \mathbf{E} = \epsilon_{\text{rel}} \epsilon_0 \mathbf{E} \quad (6)$$

$$\epsilon_{\text{rel}} = 1 + \chi \quad (7)$$

In CGS-Gauss units:

$$\mathbf{P} = \chi \mathbf{E} \quad (8)$$

$$\mathbf{D} = \epsilon \mathbf{E} \quad (9)$$

$$\epsilon = 1 + 4\pi \chi \quad (10)$$

Note: the dielectric constant $\epsilon = \epsilon_{\text{rel}}$ is dimensionless and has the same numeric value in both systems of units. But the susceptibility χ — which is also dimensionless — differs between the two systems by a factor of 4π , $\chi[\text{MKSA}] = 4\pi \times \chi[\text{Gauss}]$.

COULOMB FORCE IN A DIELECTRIC:

$$\text{In MKSA units } F = \frac{1}{4\pi \epsilon_{\text{rel}} \epsilon_0} \times \frac{q_1 q_2}{r^2} \quad (11)$$

$$\text{In CGS-Gauss units } F = \frac{1}{\epsilon} \times \frac{q_1 q_2}{r^2} \quad (12)$$